

InteliLite MRS 16

Next generation of the most advanced Manual & Remote Start (MRS) gen-set controller



- > Direct communication with EFI engines
- > Total remote monitoring and control
- > Cloud-based monitoring and control via WebSupervisor
- > Geo-fencing and tracking via WebSupervisor
- > Wide range of communication capabilities via RS232, RS485, CAN or USB, Ethernet, GPRS or 4G, Modbus and SNMP protocols
- > Internal PLC support, PLC editor, PLC monitor included in InteliConfig
- > Active SMS and emails in different languages
- > 2x 10 A binary outputs for cranking and fuel solenoid
- > 4 analog inputs / 7 binary inputs / 7 binary outputs on board
- Option for additional I/Os over modules
- > Flexible event based history with up to 350 events
- > Tier 4 final support
- > Load shedding and dummy load
- > Activation of binary outputs based on analog inputs
- > Multipurpose flexible timers
- > True RMS measurement
- > Version for low temperature also available
- > Maintenance timers can count to negative*
- > Internal or ECU source for running hours*
- > Analog inputs configurable as Binary or Tristate*
- > Selectable Power-up default mode*
- > Dual AMF/Dual MRS function**
- > Current and Voltage unbalance protection

Order code

IL3MRS16BAA

*From firmware 1.6 **From firmware 1.7